

TECHNICAL FEATURES

MODEL: AT.EIFFEL MARENGO
SIZE: 30,3x61,3
THICKNESS(mm): 9
DATE: 09/03/2023
CODE: 015.722.0028.09230
GROUP: GROUP BIa UNE-EN 14411 Annex G / SASO ISO 13006:2018 Annex G
TILE TYPE: GL
FINISH: MATT
FAMILY: PORCELAIN TILES (COLOURED BODY)
NUMBER OF DESIGNS: 24



TEST	RESULT
UNE-EN ISO 10545-2	DIMENSIONAL FEATURES COMPLIES WITH THE STANDARD
UNE-EN ISO 10545-3	WATER ABSORPTION <= 0,5 %
UNE-EN ISO 10545-4	MODULUS OF RUPTURE - BREAKING STRENGTH 1600-2400 N
	MODULUS OF RUPTURE - BENDING STRENGTH 35-45 N/mm2
UNE-EN ISO 10545-6	RESISTANCE TO DEEP ABRASION (MM3) <130 mm3
UNE-EN ISO 10545-7	RESISTANCE TO SURFACE ABRASION -
UNE-EN ISO 10545-8	LINEAR THERMAL EXPANSION <7,0 x 10⁻⁶ °C⁻¹
UNE-EN ISO 10545-9	THERMAL SHOCK RESISTANCE RESISTS
UNE-EN ISO 10545-11	CRAZING RESISTANCE RESISTS
UNE-EN ISO 10545-12	FROST RESISTANCE RESISTS
UNE-EN ISO 10545-13	CHEMICAL RESISTANCE - AMMONIUM CHLORIDE 100 G/L A
	CHEMICAL RESISTANCE - SODIUM HYPOCHLORITE 20 MG/L A
	CHEMICAL RESISTANCE - HYDROCHLORIC ACID 3% COMPLIES WITH THE STANDARD
	CHEMICAL RESISTANCE - CITRIC ACID 100 G/L COMPLIES WITH THE STANDARD
	CHEMICAL RESISTANCE - POTASSIUM HYDROXYDE 30 G/L COMPLIES WITH THE STANDARD
UNE-EN ISO 10545-14	STAIN RESISTANCE - GREEN AGENT IN LIGHT OIL 5
	STAIN RESISTANCE - IODINE SOLUTION IN ALCOHOL 5
	STAIN RESISTANCE - OLIVE OIL 5

SLIP RESISTANCE

TEST		RESULT
UNE 41901:2017 EX	SLIP RESISTANCE (PENDULUM)	CLASE 3
DIN 51130	CRITICAL ANGLE OF SLIP (INCLINED PLATFORM)	R11
DIN 51097	CRITICAL ANGLE OF SLIP. WET-LOADED BAREFOOT AREAS	C
BS7976 (PTV) WET	CLASSIFICATION ACCORDING TO PENDULUM TEST VALUES (PTV) WET	36+
ANSI A326.3	DYNAMIC COEFFICIENT OF FRICTION (DCOF) OF RIGID FLOORS.	-

TEST		VALOR UPEC
	UPEC CERTIFICATION	-

Declaration of Performance:

https://www.pamesa.com/ERP/4.0/empresas/151/045/ficheros/t00030006/113/DdP_DoP_N003CPR2013.pdf

TECHNICAL DEPARTMENT
PAMESA CERÁMICA

